



Model Number Nomenclature

33T00-250312-1057 ACB Model Number Nomenclature

Code	Unit Configuration	Code	AC 60 HZ	AC 50 HZ	Code	Exterior Finish
M	Motor Shaft	A	115V / 1 PH		0	None
S	Type P - Spiral	B	220-240V / 1 PH	220-240 V / 1 PH	4	#4 Satin Metal Finish
P	Protective Canopy	C		220 V / 1 PH	A	Anodized
T	Type T - Standard	E	277V / 1 PH	220-240 V / 1 PH	B	Black Oxide
R	Remote Motor	F		180-260 V / 1 PH	C	Colored Plastic
		G	208-230V / 3 PH	200-240 V / 3 PH	P	Galvanized Steel
		H	200-220V / 3 PH	200-220 V / 3 PH	M	Powder Coat Paint
		J	415V / 3 PH	415 V / 3 PH	N	Mill Finish
		K	575V / 3 PH		V	Nickel Plating
		L	208-230V / 1 PH	220 V / 1 PH	Y	Passivation Coating
		M	460V / 3 PH	380-420 V / 3 PH		Spray Paint
		N	460V / 3 PH			
		P		380-420 V / 3 PH		
		Q	208-230 460V 3PH	208-230 460V / 3PH		
		R	380 V / 3 PH			
		X	208-230 380-460V 3PH	380-420V / 3 PH		
		Y	115 V / 1 PH / 400 HZ			
		Z	115 V / 3 PH / 400 HZ			
		S	SHAFT - MOUNTED			
		D(#)	DIRECT CURRENT (VOLTAGE)			

Code	Filtration
F10	10 µm
F2.5	2.5 µm
F1	1 µm
F0.3	0.3 µm
FH	HEPA

Code	Hazardous Location
N	None
H	Harsh Duty
E	Explosion Proof
Group(s):	
[A] Acetylene	[E] Metal Dust
[B] Hydrogen	[F] Carbon-based
[C] Ethylene	[G] Nonconductive Dusts
[D] Propane	
Class	I II III
Division	0 1 2

Airflow (Nominal)	
0	0-50 CFM
1	50-125 CFM
2	125-175 CFM
3	175-275 CFM
4	275-400 CFM
5	400-500 CFM
7	500-700 CFM
8	700-850 CFM
10	850-1400 CFM
20	1400-2500 CFM
35	2500-4500 CFM
50	4500-6000 CFM
75	6000-8000 CFM
100	8500-12000 CFM
150	12000-17000 CFM
#	# X 1000 = CFM

Code	Heat / KW
N	No Heat
1	1 kW
2	2 kW
3	3 kW
4	4 kW
5	5 kW
6	6 kW
7	7 kW
8	8 kW
9	9 kW
10	10 kW
...	... kW

Cabinet	Impeller
Code	Material
A	ALUMINUM
C	CELCON
D	LDPE
F	FIBERGLASS
L	ABS
P	POLYPROPYLENE
R	FIBERGL. REINFORCED POLYAMIDE
T	STEEL
Y	POLYSTYRENE
4	STAINLESS STEEL 304
6	STAINLESS STEEL 316

Additional Options / Special Conditions / Custom Modifications

- AB -	Air Curtain Attachment	- P X -	Purge and Pressurization Type (X,Y, or Z)
- AC -	Cooling Element Included	- PF -	Mounting for Post Filter (x) µm
- B -	Base	- Q -	Supplemental Sound Dampening
- CS -	Ceiling Suspended	- R -	Rectangular Cabinet
- EC -	Electronically-Commutated	- RM -	Roof Mounting Kit
- F -	Flexible Duct for Clean Air Discharge	- SM -	Stand Mounted
- FD -	Flange on Debris Discharge for Duct or Bag	- T -	Thermostat Included
- FF -	Flange on Clean Air Discharge for Duct	- UV -	UV Light Module
- H -	Humidistat Included	- VIB -	Unit Modified to Resist Vibration
- NE -	No Electronics	- WM -	Wall Mounting Kit
- HT () -	High Temperature (?°)	- WD -	Washdown Motors
- LR -	Lifting Rings	- MOD -	Custom Modification Specified By Customer
- LT () -	Low Temperature (?°)		